

Warrior lite AC

(Q230000000)

High performance, simple-to-use, and compact blood & IV fluid warmer for operating rooms and intensive care units

September 2025 | Version 2.1



Key Benefits:

- **Simple to Operate:** Fail-safe assembly; one-button operation that minimises the likelihood of human errors and enables consistent care in mass casualty event
- **Immediate Warming:** Warm fluids in less than 11 seconds
- **At Any Input Temperature:** Even at 4°C / 39°F fluid input temperature
- **Even At High Flow Rates:** Up to 180ml/min for the full warming range (4°C - 38°C / 39.2°F - 100.4°F)
- **Unmatched Handling of Push-Pull / Bolus / Intermittent Resuscitation Method:** Fast reaction to flow changes and unmatched intermittent flows handling (e.g. hand pump, syringe, etc.)
- **Communicative:** Built-in LED display
- **Upgradeable to Full Portability:** Smooth upgrade path to portability by adding a battery
- **No Calibration:** No need for periodic calibration
- **Zero Maintenance:** 5 years between service cycles
- **Patent-Protected Smart Warming Technology:** Microprocessor-controlled smart warming technology that measures fluids temperature 100s of times a second and automatically adjusts warming to maintain 38°C / 100.4°F output.
- **Safe Technology:** Gradual warming; real-time temperature sensing with auto-adjustments and visual indications; aluminum free (heat exchanger using medical grade stainless steel)
- **Field Proven Technology:** In clinical use since early 2014 with hundreds of end users and >100K field utilisations
- **Affordable Consumables:** Cost effective consumable design
- **One Consumable Unit Fits All Warrior Products**
- **Continuum of Emergency Care:** Consumable unit fits all blood and IV fluid protocols and can be used across the entire continuum of emergency care, simplifying patient handoff between emergency settings and reducing costs



Warrior lite AC



(Q230000000)

Performance:	
Set-Point Temperature	38°C (±2°C) / 100.4°F (±3.6°F)
Warming Time	Less than 11 seconds
Minimum Delivery Rate	KVO or 2 ml/min
Maximum Delivery Rate at 4°C/39.2°F Input ^{[1] [2]}	180 ml/min
Maximum Delivery Rate at 20°C/68°F Input ^{[1] [2]}	270 ml/min
Physical Characteristics:	
Dimension (H x W x L)	22 x 12.5 x 10 cm 8.66" x 4.92" x 3.93"
Weight	1.46 kg / 3.22 lb
Electrical Characteristics:	
Electrical Specifications	100-240VAC 50-60Hz; 2.2-5.3A
Target Regulatory Envelope:	
Certifications	CE, FDA & Health Canada
IEC	<ul style="list-style-type: none"> • IEC 60601-1 • IEC 60601-1-2:2014 (EMC standard 4th edition)
Environmental Specifications:	
Storage Conditions	-20°C to 70°C (-4°F to 158°F) & 93% RH
Operating Conditions	-5°C to 50°C (23°F to 122°F) & 90% RH
Atmospheric Pressure /Altitude	700 to 1,060 hPa / -400 to 3,200 metre (-1,312 to 10,499 ft)
Ingress Protection (IP)	IP22

Core Components:

Base Unit: (QIF03-BUA1000)
Hosts the control module and user indications.
Connects with the battery and the Compact Disposable Unit

Power Supply Module (QIF-ACL10000)
Medical grade power supply module in a dedicated case

Disposable Unit:

Compact Disposable Unit (QPORT0500)
Compact sterile Disposable

Accessories:

Extension Cable (QIF-CBL00019)
To extend the connection between the base unit and the disposable unit

Mounting Unit (QIF03-MUA1000)
To secure the Warrior lite AC to pole or rail

CDU Secure Basket (QIF-MCH00041)
To secure the disposable unit to the bed

Online Training:



[1] Using standard IV kit and a 14G catheter. Blood products' flow rate may differ due to their viscosity.
[2] This document is based on EU-approved spec. The product is not yet cleared for distribution in the USA.

Note: the information provided in the Instructions For Use (IFU) shall govern in case of conflict. This document is adjusted to CE approvals; for exact specifications of the USA-cleared version, please refer to the relevant IFU or contact your QinFlow representative.	°C = degree in Celsius °F = degree in Fahrenheit Standard " = Inch AC = Alternate Current BU = Base Unit CDU = Compact Disposable Unit	cm = centimeter DU = Disposable Unit EN = European Norms FDA = Federal Drug Administration Ft = Feet g = gram	hPa = hecto Pascal (100 Pascal) HxWxL = Height x Width x Length IEC = International Electrotechnical Commission IFU = Instructions for Use IP = Ingress Protection rating IV = Intravenous	Kg = kilogram KVO = Keep Vein Open lb = Libra (Pound) MIL-STD = Military Standard ml/min = milliliter per minute RH = Relative Humidity
---	---	--	---	--